



## PLC-XW65

- Easy-to-carry projector with a net weight of only 1.6 kg
- 2,500 ANSI lumens and XGA resolution provide a bright and detail-oriented projection
- Wide angle lens with 1,2 optical zoom allows flexible positioning (1.33–1.62 : 1)
- Automatic set-up (source recognition, keystone-correction and PC-adaption) enables operation within seconds
- Anti-theft function through PIN code lock, Key lock
- Direct Power On/Off allows switching the projector on/off without delay
- 3 years warranty, 1 year lamp warranty

## PLC-XW65

TECHNICAL DATA	PLC-XW65
EAN Code	4994334261663
Category	Business & Education
Panel	3 x 0.63 " TFT p-Si (4:3), micro lens
Panel type	Organic LCD panel
Lamp	175 W UHP (LMP-129)
Brightness	2500 ANSI lumens
Brightness (eco mode)	1950 ANSI lumens
Lamp life	3500 h (eco mode) / 2000 h (normal mode)
Fan noise	30 dB (eco mode) / 34 dB (normal mode)
Standard lens	F = 1.77 - 1.99 / f = 17.4 - 21.1 mm *
Throw Distance Ratio	1.33 - 1.62 : 1
Throw Distance	1.1 - 10.0 m
Contrast ratio	600 : 1
Resolution in pixels	1,024 x 768 (XGA)
Image size min. - max. (diagonal):	40 - 300 inch
Uniformity	85 %
Bandwidth/Frequency	140 MHz, Horizontal : 15 - 100 kHz, Vertical : 50 - 100 Hz
Colour systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: D-Sub15 (RGB/Component/S-Video) Input 2: D-Sub15 (RGB) or Monitor Out Input 3: RCA (Composite) Audio: 3.5 mm Stereo Jack Audio: 2 x RCA (R/L mono) Audio output : 3.5 mm Stereo Jack Control Input Jack : Mini DIN 8 (RS232)
Audio function	1.0 W mono
Keystone correction	vertical +/- 20°
Up/Down ratio	o 6:1 (Fixed U/D Ratio)
HDTV compatibility	480i, 480p, 575i, 575p, 720p, 1,035i, 1,080i
Computer compatibility	U-XGA, S-XGA, S-XGA+, W-XGA, XGA, S-VGA, VGA, Mac
Zoom/Focus	1.2 x/manual
Power consumption	185 W (eco mode) / 225 W (normal mode), 4 W (stand-by mode)
Voltage	100 - 240 V
Warranty	3 years, 24-hr replacement service (D/CH/IT/FR - except overseas), 1-year lamp warranty (max. 2,000 hours)
Dimensions (W x H x D)	265.0 x 74.1 x 189.0 mm
Weight (Net)	1.6 kg
Standard accessories	IR remote control, Batteries, User manual, Power cable, D-Sub15 cable, PIN code label, Carrier bag, Lens cover with cord
Optional accessories	SCART/D-Sub15 cable (POA-CA-SCART), Remote control with laser pointer (POA-RCKIT03), Components/D-Sub15 cable (POA-CA-COMPVGA), Presentation kit including mouse function (POA-RCKIT04), Ceiling mount 15 cm (POA-CM01), Ceiling mount 40-70 cm (POA-CM02), Ceiling mount 70-110 cm (POA-CM03)
Lenses	Standard lens

\* You can use the distance calculator at [www.sanyo.de](http://www.sanyo.de) to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 03/2009

