



Mobility and Versatility Meets Functionality

Portable at only 3.2lbs and bright at 3000 lumens, the Vivitek D330WX projector offers a mobile and versatile presentation solution. The D330WX comes with native WXGA (widescreen) resolution, various connectivity options and quick on/off features. With DLP®/BrilliantColor™ technologies, the Vivitek D330WX delivers astounding images to be the ideal projection tool.

Features

- Native WXGA (widescreen) resolution
- Various connectivity options, including HDMI v1.3 for digital video connections
- 3000 lumens of brightness with a 2500:1 contrast
- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Enhanced color and display adjustments
- Keypad lock feature to avoid accidental changes to the settings
- Great portability at 3.2 pounds

Specifications	
Brightness	3000 Lumens
Native Resolution	WXGA (1280 x 800)
Max. Resolution	WXGA+ (1680 x 1050)
Contrast Ratio	2500:1 (Full On/Off)
Lamp Life and Type	≈2000/3000 Hours (Standard/Economy Mode), 220W
Lamp Part #	TBD
Display Type	Single 0.65" DLP® Technology by Texas Instruments
Throw Ratio	1.53 to 1.76:1 (Distance/Width)
Image Size (Diagonal)	40" to 310" (1.0 to 7.9 m)
Projection Distance	4.9' to 32.8' (1.5 to 10.0 m)
Projection Lens	F= 2.5, f= 21.3 ~24.5 mm
Zoom Ratio	1.15:1 Manual Zoom/Focus
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible
Offset	123%
Keystone Correction	±15° Vertical
Color Spectrum	134 Million
Horizontal Scan Rate	15, 30 to 91.4 KHz
Vertical Scan Rate	43 to 87 Hz
Speaker	1 Watt Mono
Remote Control	Card-Type IR Remote
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, WXGA, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, L)
I/O Connection Ports	HDMI v1.3, VGA-In, S-Video, Composite Video, Mini-Jack Audio-In, USB (Service)
Security	Kensington® Lock Port
Weight	3.2 lbs (1.5 kg)
Dimensions (W x H x D)	8.66" x 2.8" x 7.0" (220 x 71 x 178 mm)
Noise Level	37dB/34dB (Standard/Economy Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 230W (Economy Mode), 280W (Standard Mode), <1W (Standby Mode)
Operating Temperature	41 to 95°F (5 to 35°C)
Warranty	1-Year Limited Warranty, 90-Day Lamp Warranty
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual, Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	8 14964 33510 4

