

Kompakter Solid Shine- Laserprojektor der 8.500-Lumen- Klasse

PT-RZ870

Konzipiert für intensive Nutzung und dauerhafte Helligkeit für den Einsatz im Bildungswesen, in Museen und Ausstellungen sowie für Digital Signage. 1-Chip-DLP-Projektor mit Laserlichtquelle, 8.500 ANSI Lumen und WUXGA.



KEY FEATURES

- 1-Chip-DLP-Laser, 8.500 ANSI Lumen, WUXGA
- Laserlichtquelle für hohe Helligkeit und exzellente Bildqualität
- Bis zu 20.000 Stunden wartungsfreier Betrieb dank staubfestem Optikblock und haltbarem Lasersystem
- Flexible 360°-Installation und Geometric Manager Pro-Funktion
- Kontrastverhältnis von 10.000:1

Stabiler, langlebiger Solid Shine-Laserprojektor

Kompakter Solid Shine-Laserprojektor der 8.500-Lumen-Klasse konzipiert für intensive Nutzung und dauerhafte Helligkeit für den Einsatz im Bildungswesen, in Museen und Ausstellungen sowie für Digital Signage. Bis zu 20.000 Stunden wartungsfreier Betrieb, Digital Link, Kontrastverhältnis von 10.000:1 und flexible 360°-Installation.



SPECIFICATIONS

Brightness	8,800 lm (Center)*1 / 8,500lm*2
Resolution	WUXGA
Technology	Laser 1-chip DLP
Resolution	1920 x 1200 pixels
DLP™ chip Panel size (mm)	17.0 mm diagonal (16:10 aspect ratio)
DLP™ chip Panel size (inch)	0.67 inch diagonal (16:10 aspect ratio)
DLP™ Chip Display Method	DLP™ chip x 1, DLP™ projection system
DLP™ Chip Pixels	2,304,000 (1920 x 1200) pixels
Lens	PT-RZ870: Powered zoom (throw ratio 1.7-2.4:1), powered focus F 1.7-1.9, f 25.6-35.7 mm PT-RZ870L: Optional powered zoom/focus lenses
Light Source	Laser diodes laser Class 1 (Class 3R for US models)
Screen size (diagonal) (mm)	1.27-15.24 m, 1.27-5.08 m with ET-DLE055, 2.54-8.89 m with ET-DLE030, 16:10 aspect ratio
Screen size (diagonal) (inch)	50-600 inch, 50-200 inch with ET-DLE055, 100-350 inch with ET-DLE030, 16:10 aspect ratio
Resolution	1920 x 1200 pixels
Keystone Correction Range	Vertical: ±40° (±16° with ET-DLE060, ±22° with ET-DLE085/DLE055/DLE105, +5° with ET-DLE030), Horizontal: ±15° (±10° with ET-DLE060) (cannot be operated with ET-DLE030)
Keystone correction range with optional Upgrade Kit ET-UK20	Vertical: ±45° (±16° with ET-DLE060, ±40° with ET-DLE150/DLE250 / supplied lens, ±22° with ET-DLE085/DLE055/DLE105), Horizontal: ±40° (±10° with ET-DLE060, ±15° with ET-DLE085/DLE055), When vertical and horizontal keystone are used simultaneously, correction cannot be made exceeding total of 55° .
Installation	Ceiling/floor, front/rear, free 360-degree installation
Terminals SDI In	BNC x 1: 3G/HD/SD-SDI input
Terminals HDMI In	HDMI 19-pin x 1 (Compatible with HDCP, Deep Color)
Terminals DVI-D In	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)
Terminals RGB 1 In	RGB x 1 (BNC x 5): RGB/YBPBR/YCBCR/YC/VIDEO
Terminals RGB 2 In	D-sub HD 15-pin (female) x 1: RGB/YBPBR/YCBCR
Terminals Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals Serial Out	D-sub 9-pin (male) x 1 for link control
Terminals REMOTE 1 IN	M3 x 1 for wired remote control
Terminals REMOTE 1 OUT	M3 x 1 for link control (for wired remote control)
Terminals Remote 2 In	D-sub 9-pin (female) x 1 for external control (parallel)
Terminals LAN/DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connection, 100Base-TX, compatible with PLink™, HDCP, Deep Color

Power Supply	AC 100-240 V, 50/60 Hz
Power Consumption	950 W
Cabinet Materials	Molded plastic
Dimensions (W x H x D) (mm)	PT-RZ870: 498 x 200*5 x 581 mm (with supplied lens) PT-RZ870L: 498 x 200*5 x 538 mm (without lens)
Dimensions (W x H x D) (inch)	PT-RZ870: 19 19/32 x 7 7/8 *5 x 22 7/8 inch (with supplied lens) PT-RZ870L: 19 19/32 x 7 7/8 *5 x 21 3/16 inch (without lens)
Weight (kg)*4	PT-RZ870: Approx. 23.2 kg (with supplied lens) PT-RZ870L: Approx. 22.4 kg (without lens)
Weight (lbs.)*4	PT-RZ870: Approx. 51.1 lbs. (with supplied lens) PT-RZ870L: Approx. 49.4 lbs. (without lens)
Operating environment (?/M)	Operating temperature: 0-45 °C *6, operating humidity: 10-80 % (no condensation)
Operating environment (°F/Feet)	Operating temperature: 32-113 °F *6, operating humidity: 10-80 % (no condensation)
Applicable software/application	Logo Transfer Software, Multi Monitoring & Control Software, Geometry Manager Pro
Note	Note: PT-RZ870L offer the same performance as PT- RZ870 respectively, but come without a lens. *1 Measured at center area of projector screen. Measurement method is in compliance with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped. *2 Luminance measured at center of screen. *3 Lens shift is not supported on the ET-DLE055, and the optical axis is fixed with the ET-DLE030. *4 Average value. May differ depending on the actual unit. *5 With legs at shortest position. *6 When using the projector at an altitude lower than 2,700 m (8,858 ft) above sea level, and the operating environment temperature becomes 30 °C (86 °F) or higher, the light output may be reduced to protect the projector. When using the projector at an altitude between 2,700 m (8,858 ft) and 4,200 m (13,780 ft), and the operating environment temperature becomes 25 °C (77 °F) or higher, the light output may be reduced to protect the projector.
Optical axis shift Vertical (from center of screen)	+50 %, -16 % (+40%, -16% with ET-DLE060) (powered)*3
Optical axis shift Horizontal (from center of screen)	+30 %, -10 % (+19 %, -10 % with ET-DLE060 / +28 %, -10 % with ET-DLE085/DLE105) (powered)*3
Center-to-Corner Uniformity*2	90 %
Operation Noise*2	41 dB (NORMAL) / 37 dB (QUIET1) / 35 dB (QUIET2)
Contrast*2	10,000:1 (Full On/Full Off, Dynamic Contrast Mode: 3)

URL: <https://business.panasonic.de/visuelle-systeme/Laser-Projektor/PT-RZ870>

CONTACT

Web: <https://business.panasonic.de/visuelle-systeme/contact-us>